

ANEXO CONVOCATORIA

87/2023

RENGLONES

Renglón	Especificación Técnica	Imagen
1	SWITCH POE CAPA3: Especificaciones • Switch layer 3 • 10/100/1000T (RJ-45) Copper Ports -- x20 • 100M/1/2.5/5 Gigabit Ports -- x4 • 1/10 Gigabit SFP+ Ports -- x4 • Stacking Ports -- x2 (Stacking ports can be configured as additional 1G/10G Ethernet ports when the switch is not stacked) • PoE Enabled Ports -- x24 • Switching Fabric -- 160Gbps • Forwarding Rate -- 119Mpps Power and Noise Characteristics • No PoE Load Max Power Consumption (W) -- 77 • No PoE Load Max Heat Dissipation (BTU/h) -- 264 • No PoE Load Noise (dBA) -- 44 • Full PoE+ Load Max Power Consumption (W) -- 900 • Full PoE+ Load Max Heat Dissipation (BTU/h) -- 614 • Full PoE+ Load Noise (dBA) -- 44 Power over Ethernet • Max PoE Power (W) -- 740 • 7.5W PoE Sourcing Ports -- 24 • 15.4W PoE Sourcing Ports -- 24 • 30W PoE+ Sourcing Ports -- 24 TIPO: AlliedTelesis X530L-28GPXv	